



# DIGITAL LED SIGN P10MM

## SPECIFICATIONS



**Matrix - Pixel Height 32 Matrix - Pixel Width 32 Overall Pixel Pitch 10mm Video Frame Rate 60 FPS**

**Brightness Level Adjustable > 10,000 nits**

**Color Output 256 million color combinations  
Viewing Angle Vertical - 120°  
Viewing Angle Horizontal - 120°**

**Temperature Environment Sensors (opt)  
Programmic Brightness**

**Dimming 100,000 Hours Pixel Operating Lifespan  
Service Access Front And Rear Design**

**Vision Cloud Based Software  
Supported File Types: gifs, jpeg, png, wmv, swf, fla, mov, mp4**

**Line Display 2 lines per module @ 6" characters  
Update Messages From Anywhere Ideal**

**Viewing Distance 50' - 150'  
Screenshot And See Whats Playing Now**

**Voltage 120 V AC  
1 Circuit Per Side Recommended**

**10 - 15 Amp Draw Average  
Memory Backup In Case Of Loss Power**

**UL Listed  
5 Star Quality Check Guide**

**Louvred Anti Vandal Screen Protectors  
5 Year Limited Warranty**

**Year Round Technical Support Team  
Help desk And Troubleshooting Tech**

### P10 LED MODULE



**WIFI COMMUNICATION:**  
is subject to a direct line of sight between both transmitting antennas 4G communication: not responsible for periodic outages due to network coverage.

